

TURBO4FIFTY



Gianni
Ferrari





GTM - GSM
15,5-16 hp



GTR
16-21 hp



GTS
22-23 hp



GT
28 hp



TURBO Z
22-40 hp



TURBOGRASS
22-23 hp



PG - SR
22-28 hp



TURBO 1-1W-2-4
28-50 hp



TURBOLOADER
22-44 hp

TURBO4FIFTY



**Gianni
Ferrari**

TECHNICAL FEATURES

▶ Model	Turbo 4 Fifty
▶ Engine	
Fuel / Injection	Diesel / Direct
Model	Kubota V2403-M
Power / Displacement	50 hp / 2.434 cc.
No. Cylinders / Cooling	4 / Liquid
Fittings	Pressure lubrication system with gear pump – fuel filter with prefilter – cyclone-type air filter with self cleaning prefilter
Fuel tank capacity	40 L
Eco-Drive™ mode	Yes
▶ Hydrostatic transmission	
Driving wheels	Permanent 4WD
Transmission type	Variable displacement axial piston pump. Variable displacement axial piston motors on both front and rear gear drive axles with deep reduction gears
Maximum speed	12-24 km/h (2 speed)
Traction control	HTC-VD™ system – mechanical differential lock on front axle
Forward - reverse motion	2 pedals (forward foot pedal + reverse foot pedal) - with Dynamic Engine Control (DEC™)
Brakes	Hydrostatic service brake (neutral position). Dual disc parking brakes on front axle
Steering system	Power steering wheel, reduced-radius steering on rear wheels
▶ Wheels	
Front wheels size	24 x 12 - 12
Rear wheels size	20 x 10 - 8
▶ Power Take-Off	
Type / Engagement	Mechanical, with PTO shaft / Electro-hydraulic engagement by PTO button
Auxiliary hydraulics	2 double-acting quick-release couplings
▶ Front linkage	
Type	Hydraulic with 2 arms
▶ Collecting system (optional)	
Type	Built-in turbine-assisted collection. Turbine fan with 6 curved rotor blades easy to replace. Turbine can be disengaged apart from PTO
Collector	High impact resistant polyethylene, with anti-clogging audible buzzer warning of full load. Motorised spreader for full packed load. Removable large capacity filtering screen for maintenance
Collector capacity	1400 L
▶ High-lift dump (optional)	
Maximum emptying height	230 cm
Overhang at maximum height	30 cm
▶ Driver's seat	
Steering wheel	Steering wheel with knob and tilt adjustable steering console arm
Seat	Delux Grammer seat with lumbar support and headrest. Adjustable armrest and backrest.
Seat suspension	Pneumatic suspension with infinitely variable air-assisted height adjustment. 50 to 130 kg adjustment, 100 mm stroke.
▶ Electrical system	
Battery	12 V / 100 Ah – battery isolator master switch as standard
Safety sensors	EEC European Standard / ISO
Warning system	Engine oil pressure – fuel reserve – battery (alternator fault) – hydraulic oil filter restriction – hydraulic oil temperature – parking brake – coolant temperature – coolant level warning – hydraulic oil level warning
Standard equipment	Hour meter – tachometer – fuel level – coolant temperature gauge – Full road light kit with rotating beacon
▶ Weight and measures (tractor unit only, basic version)	
Unloaded weight	1.250 kg
Length / Width / Height	285 x 125 x 186 (200)* cm

* with ROPS folded down (upright)

The availability of models, versions and trim may vary depending on the country.

- ▶ **ATTACHMENTS: NEW** 180 RCA collecting deck, **NEW** 160 Dual-Cut™ mulching and rear discharge deck, collecting deck RCA 150 cm, side discharge deck 150 cm, rear discharge deck 165 cm, flail mower 120 and 150 cm, sweepers, winter maintenance attachments, etc.



www.gianniferrari.com